

PS501-56120-00



Pixel Scientific, Inc.
4 Carbonero Way | Suite B
Scotts Valley, CA 95066
Phone: 408-659-4630
www.pixelscientific.com

Custom Displays

Key Features:

- Sunlight Readable
- Custom Sized LCD
- LED Backlight
- Low Power Consumption
- Slim Bezel Design
- Long Life Expectancy

This is an innovative, ultra-wide, sunlight readable, LED Backlight, TFT LCD display. It is a 4k resolution, high color saturation display intended for wide stretch applications, digital signage, digital signage, public transportation, exhibition hall, department store, and industrial applications. The monitor includes a host PC. It can be used in many applications requiring high brightness, sunlight readable, high-quality video and energy-efficiency.



56.2" x 11.8" Custom Sized AMLCD
with High Bright Backlight (Double Sign)
3840 x 807

Description: 56.2" x 11.8" Custom Sized AMLCD with LED Backlight 3840 x 807

Display Area (mm)	1428.5(H) x 300.2(V)	Response Time	9.5 ms
Brightness	1000 cd/m ²	LCD Interface	V-by-One
Resolution	3840 x 807	Operating Temperature	(0°C ~ 50°C)
Aspect Ratio	16:3.4	Storage Temperature	(-20°C ~ 60°C)
Contrast Ratio	5000:1	Power Consumption	260W
Pixel Pitch	374 μm	Dimensions (mm)	1468(W) x 340(H) x 67.4(D)
Viewing Angle	178°(H), 178°(V)		Each Display IP54 enclosed
Color Saturation	83%	LED Driver	Included
Display Colour	1.07G	Controller Interface	PC Box (Intel Skylake)
		OSD Button	Power Switch, Menu, Select (+,-)